

DOE Office of Nuclear Energy Integrated Energy Systems: Program Overview

Shannon Bragg-Sitton, Ph.D.

Director, Integrated Energy & Storage Systems National Technical Director, DOE-NE Integrated Energy Systems shannon.bragg-sitton@inl.gov

Idaho National Laboratory

INL/MIS-22-66404


March 17, 2022


Motivation and challenges

- Evolution in the electric power sector
 - Advent of variable renewables \rightarrow increased variation in net load
 - Transition away from traditional baseload resources
 - Increased need for generator flexibility while ensuring grid resilience, reliability
- Ambitious goals for deep decarbonization ("net-zero")
 U.S. targets:
 - Zero emissions from electricity sector by 2035
 - Economy-wide net-zero emissions by 2050 \rightarrow industry, transportation
- Traditional energy planning tools are often limited in applicability to new scenarios, technologies, opportunities
 - Cross-sectoral energy utilization from a single generator not represented



Operational paradigms—nuclear energy flexibility





IES

3

Integrated Energy System (IES) needs: Technology advancement for energy transport, conversion, and storage

Integrated Energy Systems Involve


- Thermal, electrical, and process intermediates integration
- More complex systems than co-generation, poly-generation, or combined heat and power
- May exploit the economics of coordinated energy systems
- May provide grid services through demand response (import or export)

Technology Development Needs & Opportunities

- New energy storage technologies (thermal, chemical, and electrical)
- Thermo-electrical chemical conversion processes
- Modern advanced informatics and decision systems for massive data
- Embedded sensors for health monitoring
- Cyber security approaches


Example: Nuclear-driven IES in the U.S. Midwest

(notional)



https://ies.inl.gov

DOE-NE R&D Programs for Multi-Output Integrated Energy Systems



Crosscutting Technology Development **Integrated Energy Systems**

VISION

A robust and economically viable fleet of light-water and advanced nuclear reactors available to support US clean baseload electricity needs, while also operating flexibly to support a broad range of non-electric products and grid services.

Flexible simulation ecosystem for system design, analysis, technical and economic optimization

Experimental demonstration for technology development and model validation

Greenfield system design and advanced reactor applications Reduce risk for commercial LWR-IES deployment

Energy dispatch design and implementation

Technical and economic analysis, near-term markets

> Safety assessment and licensing considerations

Light Water Reactor Sustainability Program

INL/EXT-20-59585

Flexible Plant Operation and Generation **Technical Program Plan for FY 2021**



September 2020 U.S. Department of Energy Office of Nuclear Energy

Flexible Plant Operations & **Generation Pathway**



Timeline for Deployment

earated Enerov Svstems

Current fleet **NOW**—Advanced Reactors **5-15 years**



IES Program Overview

Mission: Maximize energy utilization, generator profitability, and grid reliability and resilience through novel systems integration and process design, using nuclear energy resources across all energy sectors in coordination with other generators on the grid.


Vision: A robust and economically viable fleet of light-water and advanced nuclear reactors available to support US clean baseload electricity needs, while also operating flexibly to support a broad range of non-electric products and grid services.

Goals: The IES program develops tools and technologies that will lead to demonstration of multiple integrated energy systems that have a clear path toward commercialization. Timelines follow the associated reactor concepts and designs (current fleet now, SMRs 1-5 yrs, non-LWR 5-15 years).

6

Strategic R&D Areas (Control Accounts)

- System Simulation. Develop and exercise an ecosystem for modeling, analysis, optimization of IES that can accommodate various reactor types, renewable technologies, and energy users.
 - *Economic Analysis.* Establish a reference capability to validate current practices in valuing nuclear energy in the energy market (electric and non-electric).
- **Experimental Evaluation**. Establish and operate a fullyfunctional and diverse non-nuclear facility for model validation and initial technology demonstration.




Summary of potential nuclear-driven IES opportunities



Integrated Energy Systems

Reactor sizes align with the needs of each application, heat augmentation can be applied if needed to match process temperature demands.




https://ies.inl.gov

IES M&S Tools: Purpose

Technoeconomic Assessment Analyses for IES

- Portfolio Optimization
- Dispatch Optimization
- Process Model Simulation
- Economic Analysis
- Supervisory Control
- Stochastic Analysis
- Workflow Automation



Integrated Energy Systems




APS Case Study 2019 – Desalination



Arizona Public Service (APS) challenge




- "Classic" considerations:
 - Wear and tear of plant component (difficult to determine)
 - Negligible variable costs, e.g., fuel cost (true?)
 - Electric grid price will be negative (how to assess this?)
- Another option: Desalination
 - Change in water procurement costs
 - Other lower cost water sources available (brackish water)






Potential Scenarios




11


Case 1: Desalination for Plant Cooling




Case 2: Desalination for Plant Cooling plus Potable Water



Potential Scenarios




Potential Scenarios



https://ies.inl.gov

Analysis shows economic feasibility of implementing onsite desalination at Palo Verde Generating Station


- Results demonstrated to industry partners onsite desalination (RO1) was unnecessary
- Demonstrated to maximize profits RO2 could be built larger given regional water demands
 - The primary constraint on lowcost water is creating larger effluent ponds to store excess brackish water



Exelon Case Study 2019 – Hydrogen Production coupled with an Existing LWR




Example: Multiple Generators for Hydrogen Production




https://ies.inl.gov

Example: Disruptive potential of nuclear produced hydrogen


- Collaboration between INL, ANL, NREL, Exelon, and Fuel Cell Energy
- **Goal:** Evaluate the potential of using existing nuclear plants to make hydrogen via high temperature steam electrolysis (HTSE) in parallel to grid electricity to enhance LWR economics
- Approach: Techno-economic analysis of HTSE process in selected operating modes and market conditions
 - Electricity only (business as usual)
 - Dynamic H₂ production (with H₂ storage to enable variable electricity and H₂ dispatch)
- Assumptions
 - HTSE does not thermally cycle
 - Dedicated H₂ transport pipelines
 - No subsidies for avoided emissions
 - Ancillary services market not considered
 - H₂ demand must always be met



Example: Disruptive potential of nuclear produced hydrogen



LWR-HTSE LCOH as a function of electricity price compared to the SMR plant (with and without carbon capture sequestration [CCS]) LCOH with low, baseline, and high natural gas pricing. 18



- Analysis tools used to determine optimal dispatch of electricity to meet grid demand (high grid prices) or to produce H2 (low grid prices)
- H₂ is alternate stored or dispatched from storage to ensure the H₂ market demand is also met at all times



https://ies.inl.gov

Example: Disruptive potential of nuclear produced H2

- Results •
 - Low grid pricing \rightarrow hydrogen is more profitable
 - High grid pricing \rightarrow sale to the grid is more profitable
 - H₂ storage provides flexibility in plant operations, ensures that all demands are met
 - H₂ off-take satisfies demand across steel manufacturing, ammonia and fertilizer production, and fuel cells for transportation
- Analysis results suggest a possible revenue increase of \$1.2 billion (\$2019) over a 17-year span

Nine Mile Point Nuclear Power Plant LTE/PEM Vendor



- Outcome: Award from the DOE EERE Hydrogen & Fuel Cell Technologies Office with joint Nuclear Energy funding for follow-on work and low temperature electrolysis demonstration at Exelon Nine-Mile Point plant; anticipate hydrogen production ~Fall 2022.
- Full report: Evaluation of Hydrogen Production Feasibility for a Light Water Reactor in the Midwest (INL/EXT-19-55395) Integrated Energy Systems

Nuclear-H₂ production demonstration projects



Constellation (Exelon): Nine-Mile Point NPP

- 1 MWe Low Temperature Electrolysis (LTE)/PEM, nel hydrogen
- Using "house load" power
- PEM skid testing underway at NREL
- H₂ production beginning ~October 2022
- Energy Harbor: Davis-Besse NPP
 - 1-2 MWe LTE/PEM Vendor 2
 - Power provided by completing plant upgrade with new switch gear at the plant transmission station
 - Installation to be made at next plant outage
 - Contract start October 2021; H₂ production ~2023/24
- Xcel Energy: Prairie Island NPP
 - 150 kWe High Temperature Electrolysis (HTE)/SOEC Vendor 1
 - Tie into plant thermal line engineering is being planned
 - Design complete Q4 2022; Installation, testing complete Q1 2024

APS/PNW Hydrogen: Palo Verde Generating Station

- 15-20 MWe LTE H2 production, ~6-8 tons H2/day
- Co-locate H₂ production at the site of use
- H_2 storage + H_2 to gas peaking turbines (50%), syngas pilot
- H₂ production expected early 2024

https://ies.inl.gov

🜔 aps

Nine Mile Point Nuclear Power Plant LTE/PEM, nel hydrogen



Thermal & Electrical Integration at Xcel Energy Prairie Island NPP HTE/Vendor 1 Davis-Besse Nuclear Power Plant LTE-PEM Vendor 2



Palo Verde Gen Station Hydrogen Production for Combustion and Synthetic Fuels



@Scale







Exelon.


energy harbor

Advanced reactor IES case studies (FY22)

- Thermal energy storage: Utilization of thermal energy storage to support electrical markets and/or industrial integration
- Synthetic fuel production: Nuclear heat and steam to produce hydrogen; then, as a feedstock, the hydrogen is used in conjunction with a CO2 source to produce various high value synthetic fuels via the Fischer-Tropsch process
- Carbon conversion: Nuclear heat and steam to convert coal, as a feedstock, into valuable products for a variety of carbon markets



Nuclear–Thermal Energy Storage Case Study



coupled thermal energy storage




https://ies.inl.gov

inform case selection

Nuclear–Carbon Conversion Case Study

Goal: Use an advanced reactor to generate steam, heat, and electricity for a coal conversion plant.



Nuclear–Synthetic Fuels Production

Goal: Demonstrate the economic potential of using advanced nuclear reactors for synthetic fuels creation.

Primary Questions


- 1. Economics: Proper distribution of products to minimize economic risk.
 - Electricity sales
 - Ancillary product sales
 - Capacity sizing optimization
 - Market participation

2. Control

- Coupling and control of the units
- Dispatch optimization

Outcomes

- Optimized advanced reactor/synthetic fuel process
- Demonstration of proper coupling mechanisms with selected advanced reactors



Representation of nuclear coupled synthetic fuel production




Experimental evaluation: Model validation, technology demonstration, performance characterization, control system development




Dynamic Energy Transport and Integration Laboratory (DETAIL) for electrically heated testing of integrated systems





DETAIL enables cross-complex laboratory connections



National Reactor Innovation Center (NRIC) advanced reactor testing infrastructure

- Goal: Demonstrate two advanced reactors by 2025
- Strategy:
 - Repurpose two facilities at INL and establish two test beds to provide confinement for reactors to go critical for the first time
 - Build/establish testing infrastructure for fuels and components
- Capabilities:
 - NRIC DOME (Demonstration of Microreactor Experiments)
 - Advanced Microreactors up to 20 MWth
 - High-Assay Low-Enriched Uranium (HALEU) fuels < 20%
 - NRIC LOTUS (Laboratory for Operations and Testing in the US)
 - Up to 500 kWth experimental reactors
 - Safeguards category one fuels
 - Experimental Infrastructure
 - Molten Salt Thermophysical Examination Capability
 - Helium Component Test Facility







Anticipate initial reactor testing in ~2024. Flexible testbed to support testing of multiple reactor concepts using the same infrastructure ~annually.



For more information on NRIC and to download resources, see https://nric.inl.gov/.





Idaho National Laboratory





WWW.INL.GOV